



TRADITION. QUALITÄT. LEIDENSCHAFT.

R&R RIDING TRACK DRAG

Ideal for thin surface layers and sand ground

The riding track drag optimally meets the changed structure of today's riding arenas. It produces reliable leveling of the upper surface without endangering the sensitive substructure. Two angle section chisels break up the surface which is then distributed and compacted with the rounded blade.

The rake frame, with replaceable rake, is continuously adjustable in height. Additional sliding rails guarantee long durability. The device with wall lining scraper and roller wheel is available for tractors of 30 HP and upwards. Of course all basic fabrication is in galvanized steel.



Article number	Width	Weight	Blades / Rake teeth	Net price ex VAT
RBS 200 (for tractors from 30 hp)	2,00 m	210 kg	10 / 15	2.200,00 €
RBS 250 (for tractors from 40 hp)	2,50 m	240 kg	13 / 19	2.380,00 €
RBS 300 (for tractors from 50 hp)	3,00 m	270 kg	14 / 23	2.560,00 €

RÖWER & RÜB

LEBENSÄRÄUME FÜR PFERDE. SEIT 1867

Röwer & Rüb GmbH Syker Straße 205-213 27321 Thedinghausen www.roewer-rueb.de
T +49 4204 9140-0 F +49 4204 9140-60 E info@roewer-rueb.de